

+86 0571 555 3535 Qian Tan Cheng Dong, Jiande, Hangzhou, Zhejiang Province astra-chemical.com info@astra-chemical.com

ASTRA DF 1504

Silicone defoamer

Description

ASTRA DF 1504 is an organosilicone defoamer for water-borne systems. It has strong defoaming ability even at low dosage. It should be introduced at the grinding stage.

Physical and Chemical properties

Ingredient:Modified polydimethylsiloxaneAppearance:Colorless viscous liquidContent:100%

Speciality

- 1. ASTRA DF 1504 defoamer is suitable for water-borne and middle and high polarity resin coating systems, it provides quick defoaming.
- 2. ASTRA DF 1504 defoamer has high defoaming efficiency even at low dosage.

Application System and Dosage

ASTRA DF 1504 is recommended for middle and high polarity resin coating systems and water-borne systems.

Usually, the recommended dosage of the additive is around 0.05 - 1.0% upon total formulation. It should be introduced at the dispersion stage during the manufacture.

Package

25kg metal pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

