

+86 0571 555 3535
Qian Tan Cheng Dong,
Jiande, Hangzhou,
Zhejiang Province
astra-chemical.com
info@astra-chemical.com

ASTRA DISP 5706

Dispersant

Description

ASTRA DISP 5706 is a polymer dispersing agent with star type structure. It has excellent wetting ability for many kinds of pigments. It could greatly decrease the mill viscosity and increase the pigment content in the pigment paste.

Physical and Chemical properties

Ingredient: Block copolymer with pigment affinity groups

Appearance: Yellow transparent liquid

Active part: 100%

Speciality

- 1. ASTRA DISP 5706 is suitable for medium polarity systems and has excellent compatibility with most of common resins.
- 2. ASTRA DISP 5706 could greatly decrease the mill viscosity and increase the pigment content in the pigment paste.

Application System and Dosage

ASTRA DISP 5706 is suitable for medium polarity resin systems and is particularly suitable for UV curable systems.

Usually, it should be introduced before the grinding stage during the manufacture with 10% to 15% dosage upon inorganic pigments, 5% to 6% dosage upon TiO2, 30% to 90% dosage upon organic pigments, 70% to 100% dosage upon carbon black.

Package

25kg metal pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

