

ASTRA LA 4901

Leveling agent

Description

ASTRA LA 4901 is a fluorosilicone modified with polyether. It could greatly decrease the surface tension and provide strong wetting ability without any negative influence on recoatability. ASTRA LA 4901 is an excellent substrate wetting and leveling agent with great hydrolysis resistance.

Physical and Chemical properties

Ingredient: Polyether modified polysiloxane

Appearance: Light yellow transparent liquid

Active part: 25%

Solvent: Diethylene glycol monobutyl ether

Speciality

Leveling	Wetting	Recoatability	Compatibility	Sliding	Low Foam Stabilization	Anti-craters	Anti-blocking
●●●●●	●●●●●	●●●●●	●●●●●	●	●●	●●●●●	●

●●●●● Good ● Bad

Application System and Dosage

ASTRA LA 4901 is suitable for the water-borne wood paints, industrial water-borne coatings, UV-curable coatings and printing inks.

The recommended dosage of the additive is 0.1 - 1% upon total formulation. It could be introduced at the random stage during the manufacture.

Package

25kg pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

